

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/054723 A1

(51) International Patent Classification⁷: **B05B 11/00**

(21) International Application Number:
PCT/GB2003/005316

(22) International Filing Date: 5 December 2003 (05.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0229099.7 13 December 2002 (13.12.2002) GB
0313474.9 11 June 2003 (11.06.2003) GB

(71) Applicant (for all designated States except US): **INCRO LIMITED** [GB/GB]; 35 Fairfield Rise, Wollaston, Stourbridge, West Midlands DY8 3PQ (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LAIDLER, Keith** [GB/GB]; 35 Fairfield Rise, Wollaston, Stourbridge, West Midlands DY8 3PQ (GB).

(74) Agents: **HILL, Richard** et al.; Wilson Gunn Skerrett, Charels House, 148/9 Great Charles Street, Birmingham B3 3HT (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: IMPROVEMENTS IN OR RELATING TO PUMP-ACTION NOZZLE DEVICES



(57) **Abstract**—In a first aspect, the present invention concerns a pump-action nozzle device (100) adapted to be fitted to a container and to enable fluid stored in the interior of said container to be dispensed during use, which has a body which defines: an internal chamber (107); an outlet (112) through which fluid dispensed from said chamber (107) is ejected from the device (100, said outlet (112) further comprising an outlet valve (105) configured to only open and permit fluid to be dispensed from the chamber (107) when the pressure therein exceeds a predetermined minimum threshold pressure; and an inlet (110) through which fluid can be drawn into said chamber, said inlet (110) further comprising a valve (108a) configured to only open and permit fluid to be drawn into the chamber (107) when the pressure within the chamber (107) falls below the external pressure. The body of the device comprises a base portion (101) and a housing portion (102), said base portion (101) and housing (102) portions together defining the internal chamber (107) of the device (100) and being slidably mounted to one another such that said housing portion (102) can be slid towards the base portion (101) to reduce the internal volume of the chamber (107) during a first stage of operation, thereby causing the pressure within the chamber (102) to increase and any fluid stored therein to be dispensed through said outlet (112) to be dispensed if the pressure therein exceeds the predetermined minimum threshold pressure required to open the outlet valve (105), and then slid away from the base to increase the volume of the chamber (107) during a second stage of operation, thereby causing the pressure within the chamber (107) to reduce and fluid to be drawn into the chamber through the inlet (110). In another aspect the present invention relates to a pump-action nozzle device which additionally comprises an air chamber (203) configured to co-eject a stream of air with liquid dispensed from the device in the usual manner.